

TECHNICAL DATA SHEET

Edition 11.08.2025  
OriGen® GrafGen  
Matt / Eggshell / Semi-gloss Finish

PRODUCT DESCRIPTION

OriGen® GrafGen is an environmentally friendly, breathable, and preservative-free exterior paint. Available in washable matte, eggshell, and semi-gloss finishes, it features proprietary  $\text{CaCO}_3$ ® technology and a next-generation Bio-Based (VAE) formulation that delivers a durable, long-lasting coating with protection against fungi and algae. Suitable for both new construction and repainting, GrafGen is ideal for surfaces exposed to high humidity. It also boasts a minimal carbon footprint, making it perfect for residential applications, indoor and outdoor decoration, and sustainable construction projects.

KEY FEATURES

- Class 1 scrub resistance (EN 13300)
- High coverage capacity
- Excellent adhesion; non-film-forming
- Highly breathable and water-repellent
- Prevents condensation
- Free from VOCs and formaldehyde emissions
- Preservative-, solvent-, and microplastic-free
- Designed according to circular economy principles
- Titanium dioxide content < 5%
- Organic content < 5%

TECHNICAL PROPERTIES

Property	Value
Specific Gravity	1.6 ± 0.05 g/cm³
pH	9 ± 1
Viscosity	100–120 U.K.
Solids by Weight	70 ± 5%
Base	Bio-Based (VAE)
Appearance	Dense liquid
Finish	Matt / Eggshell / Semi-gloss
VOC Content	< 1 g/L
Fire Resistance	B2, Sd0

---

## COVERAGE

250-350 sq.ft/gal (2 coats)

Actual coverage depends on the surface type and condition, tools used, and application method.

On-site testing is recommended to determine precise consumption.

---

## APPLICATION SURFACES

- Plaster and gypsum
- Fillers and mineral-based substrates
- Prefabricated panels
- Uncoated wallpaper
- Brick, perlite
- Other porous or mineral surfaces

---

## SUBSTRATE PREPARATION

- Ensure the substrate is clean, dry, and free from dust, salt, grease, and loose paint.
- Remove previous coatings that are not well-adhered using mechanical or pressurized water cleaning.
- If mold, algae, or mildew are present, clean thoroughly with specific biocidal products.
- For absorbent surfaces: Apply Primer L44.
- For wood, rust-free metals, or non-porous surfaces (e.g. tiles): Apply a bonding primer (*All Terrain 4x4 Primer*).
- Paints forming impermeable films must be stripped or mechanically removed.
- Mineral substrates must be at least **28 days cured**.
- Avoid applying on surfaces in permanent contact with water.
- In high humidity or contaminated environments, use a water-repellent sealer to reduce moisture and pollutant absorption.
- For unusual pathologies or special conditions, consult the Technical Department.

---

## APPLICATION CONDITIONS

- Ambient and surface temperature: **41°F to 104°F**
  - Do not apply in direct sunlight or on overheated substrates.
-

## PRODUCT PREPARATION


- Stir thoroughly before use.
- Reduce with **5–10% clean water** (approx. **13–19 fl oz per gallon**).

---

## APPLICATION METHOD

- Apply two to three uniform coats, making sure to keep a wet edge to prevent visible lap lines. Work one wall at a time, cutting in and rolling with the same dilution ratio throughout. Roll as close to the edges as possible to avoid “picture framing.” Avoid applying the product too heavily, as this can slow curing and lead to micro-cracks. Because of their mineral base, these paints perform best when they are well rolled and worked into the surface, resulting in a smooth, consistent, and rich finish.
- **Second and third coats:** Apply irregularly using a round brush or flat trowel.  
⚠️ Avoid excess product per layer to prevent micro-cracking.
- Recommended tips 315-317 or 210-312
- Recommended pressure - 1800 - 2000 psi

For technical inquiries:

 [info@origenpaints.com](mailto:info@origenpaints.com)

---

## DRYING & CURING TIMES

- **Second coat:** After 2–4 hours at **77°F** and 60% relative humidity
- **Full drying:** After 24 hours
- **Complete curing:** After 10 days — do not clean or scrub before this time to ensure optimal hardness and durability.  
*Drying time may vary with temperature and humidity.*

---

## TOOL CLEANING

Clean all tools with **warm water** immediately after use.

---

## PACKAGING FORMATS

- **0.25 gal (32 fl oz)**
- **1 gal (128 fl oz)**
- **4 gal (512 fl oz)**
- **5 gal (640 fl oz)**

---

## STORAGE CONDITIONS

- Store in original, sealed packaging
- Keep in a cool, dry place, away from frost and direct sunlight
- Maximum shelf life: **24 months** from the production date

---

## WASTE MANAGEMENT

- Follow local regulations and consult the Safety Data Sheet (SDS)
- Packaging is made of recycled plastic
- Do not dispose of waste through drains — use local recycling centers
- Reuse leftover paint whenever possible to reduce environmental impact

---

## SAFETY INSTRUCTIONS

- Refer to the latest Safety Data Sheet (SDS) for physical, toxicological, ecological, and safety data
- Keep out of reach of children

---

## DISCLAIMER

The technical values and recommendations provided are based on extensive laboratory testing and field experience. These are guidelines only and do not constitute a binding legal warranty. The end user must verify the product's suitability for each specific case and comply with applicable building standards and regulations. OriGen® reserves the right to update this information without prior notice. This edition supersedes all previous versions.