

TECHNICAL DATA SHEET

Neutralysalt Primer

Neutralysalt Primer — Anti-Salt / Anti-Efflorescence Treatment

EDITION 16.09.2026

01 PRODUCT DESCRIPTION

OriGen® Neutralysalt Primer is a 100% natural preventive and corrective treatment, formulated with next-generation biodegradable chelating agents (GLDA) to stop the migration and crystallization of soluble salts in mineral walls. It works by blocking the formation of efflorescence (saltpeter) without altering the breathability of the substrate. Free from solvents and synthetic additives, it is fully compatible with materials such as lime, clay, and silicate.

02 KEY FEATURES

- Selective chelating action on soluble salts (nitrates, chlorides, sulfates)
- Prevents surface crystallization of salts (efflorescence or saltpeter)
- Biodegradable
- Compatible with historic and ecological mineral substrates
- Preserves wall breathability
- Free from solvents and microplastics
- Simple application – no specialized equipment required

03 TECHNICAL PROPERTIES

PROPERTY	VALUE
Specific Gravity	1.02 ± 0.03 g/cm³
pH	9.5 ± 1
Appearance	Clear, transparent liquid
Odor	Neutral
Chemical Nature	GLDA chelating agent (eco-friendly technical grade)

04 COVERAGE

1,020–1,220 sq.ft/gal (25–30 m²/L)

1–2 COATS DEPENDING ON SUBSTRATE POROSITY

Actual coverage depends on the surface type and condition, tools used, and application method. On-site testing is recommended to determine precise consumption.

05 APPLICATION SURFACES

Mineral walls affected by rising damp or the presence of salts:

- Lime and clay substrates
- Ceramic brick
- Natural stone
- Ecological renders
- Mineral stuccos

 Do not apply on synthetic or varnished surfaces.

06 SUBSTRATE PREPARATION

- The surface must be dry or slightly damp, and clean of dust, grease, mold, and loose residues.
- Manually remove surface salt crusts before applying the product.

07 PRODUCT PREPARATION

- Stir thoroughly before use.
- Apply the product undiluted – no reduction or mixing required (single-component product).

08 APPLICATION METHOD

- Apply with a brush, roller, or manual sprayer.
- Perform 1 to 2 wet-on-wet applications, depending on the absorption of the substrate.
- Do not rinse or wash off after application.

For technical inquiries: marketing@origenpaints.com

09 DRYING & CURING TIMES

- Before renders or final finishes: Allow the product to act for a minimum of **24 hours**.
- After 24 hours: if the wall had algae or mold, apply **Primer L44** before the finish; otherwise, apply the finish directly.
- Drying time may vary with temperature and humidity.

10 TOOL CLEANING

Clean all tools with warm water and natural soap immediately after use.

11 PACKAGING FORMATS

- **1.3 gal (5 L)** plastic jug

12 STORAGE

- Store in the original, sealed container, in a cool place protected from direct sunlight.
- Do not expose to temperatures below **32°F (0°C)**.
- Approximate shelf life: **18 months**.

13 WASTE MANAGEMENT

- Consult the Safety Data Sheet (SDS).
- Do not dispose of the product in waterways.
- Take the empty container to a local recycling center.

14 SAFETY INDICATIONS

- Avoid contact with eyes. In case of contact, rinse with plenty of water.
- Do not ingest.
- May be corrosive to metals: keep only in the original container.
- Keep out of reach of children.