

TECHNICAL DATA SHEET

OxiGen Lime Wash White

Lime-based mineral paint · Matte finish

EDITION 17.09.2026

01 PRODUCT DESCRIPTION

OriGen® OxiGen Lime Wash is a lime-based mineral paint formulated for exterior and interior use. It is highly breathable. The finish is matte and mineral in appearance.

OxiGen Lime Wash contains high-quality artisanal lime combined with Graphene by **CACO₃® Technology**, resulting in a premium-grade, durable, and long-lasting product that promotes healthier, more sustainable environments. OxiGen Lime Wash helps neutralize CO₂ and has an extremely low carbon footprint.

Ideal for both new construction and repainting, it is perfect for decorating façades and other mineral-based substrates.

02 KEY FEATURES

- High hiding power
- Matte mineral finish
- Strong adhesion without forming a film
- Highly breathable and water-repellent
- Prevents condensation
- Free from VOC and formaldehyde emissions
- Sustainable, designed under circular economy standards
- Free of solvents and microplastics
- Titanium dioxide content < 1%
- Organic content < 5%
- Neutralizes CO₂

03 TECHNICAL PROPERTIES

PROPERTY	VALUE
Specific gravity	1.45 ± 0.05 g/cm ³
pH	13 ± 1
Viscosity	90–110 KU (Krebs units)
Solids by weight	60 ± 5%
Nature	Aerial lime
Appearance	Dense liquid

PROPERTY	VALUE
Finish	Matte
VOC content	< 1 g/L
Reaction to fire	A2-s1, d0 (UNE-EN 13501-1)
Vapor H ₂ O transfer	Sd < 0.03 m – V1
Capillarity	W2

04 COVERAGE

9–11 m²/L 365–445 ft²/gal
1 COAT 1 COAT

Coverage depends on substrate type and condition, tools used, and application method. On-site testing is recommended to determine exact consumption.

05 AVAILABLE COLORS

White.

06 APPLICATION SURFACES

Concrete, cement renders, plaster, gypsum, fillers, prefabricated panels, brick, and other mineral-based surfaces.

07 SUBSTRATE PREPARATION

- Substrates must be dry, clean, and free from dust, salts, and imperfections. If there is a lot of salt, use **Neutralysalt Primer**.
- Remove loose or poorly adhered paint manually or with pressure washing.
- Ensure surface texture is even.
- If the surface shows algae, mold, mildew, or other impurities, thoroughly clean with suitable biocidal products. **Primer White L44**.
- For walls with a disintegrating surface, apply **MinerGen** sealer as a consolidant.
- For wood, non-corroded metal, or non-porous surfaces (e.g., ceramic tiles), apply **Primer AllTerrain 4x4**.
- Old film-forming paints that block vapor diffusion or are unstable must be removed with a stripper or mechanical means.
- Mineral substrates must be at least **28 days** cured.
- Do not apply on surfaces in permanent contact with water.

- In areas exposed to high humidity or pollution (bathrooms, kitchens), apply **TerraGen PU Water-Repellent** as a protective coating to reduce water and impurity absorption. It reduces the breathability of the finish.
- For any other conditions not specified above, consult the Technical Department.

08 GENERAL RECOMMENDATIONS

- Protect all non-painted surfaces (woodwork, glass, stone, etc.).
- Shield the painted surface from rain for at least **4 days** after application.
- Clean splashes immediately with water.
- Do not mix with other products to preserve its specific properties.

09 APPLICATION CONDITIONS

- Ambient and surface temperature: **41°F to 104°F (5°C to 40°C)**
- Do not apply in direct sunlight or on overheated surfaces.
- Protect surfaces from sun, wind, and rain during and after application.

10 PRODUCT PREPARATION

- Stir thoroughly before use.
- Dilute with **5–10% water by weight** (approximately 2.3–4.6 fl oz of water per quart, or 72–145 mL per liter).

11 APPLICATION METHOD

- Apply using brush, roller, or spray gun (nozzle size ≥ 0.017 in).
- Apply **2 uniform coats**. Excessive product in a single coat may cause micro-cracking.
- For highly exposed façades, **3 coats are recommended**.

For technical assistance, contact: marketing@origenpaints.com

12 DRYING & CURING TIMES

- **Recoatable:** 2–4 hours at **77°F (25°C)** and 60% relative humidity
- **Fully dry:** 24 hours
- **Full cure:** 30 days, reaching optimal hardness and resistance
- Avoid cleaning or scrubbing the surface during the curing period.

13 TOOL CLEANING

Clean tools with **warm water** immediately after use.

14 PACKAGING FORMATS

- **1 gal** (128 fl oz)
 - **5 gal** (640 fl oz)
-

15 STORAGE

- Store in original, sealed containers in a cool place.
 - Protect from frost and direct sunlight.
 - Shelf life: **18 months** from manufacturing date.
-

16 ENVIRONMENT & DISPOSAL

- Refer to the Safety Data Sheet and comply with local regulations.
 - Containers are made of recycled plastic.
 - Respect the environment: do not pour leftover product into drains.
 - Use the nearest recycling center.
 - Reuse leftover product whenever possible to reduce paint waste.
-

17 SAFETY INFORMATION

- Always consult the latest Safety Data Sheet for full safety, health, and ecological information.
 - **Corrosive** due to its lime content (pH > 11). **H314:** Causes severe skin burns and eye damage. Wear gloves and eye protection.
 - Keep out of reach of children.
-

All values and product characteristics are based on intensive research and practical experience. Recommendations – written or verbal – serve as general guidance and do not establish a legal warranty. Users must verify the product's suitability for their specific needs. Comply with general construction regulations and standards. We reserve the right to improve or modify the product without notice. This edition supersedes all previous versions.